

# SAFETY DATA SHEET

## Roko Professional Anti-Virus, Roko Professional Anti-Virus Aloe

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830

Date of issue : 2020-03-05

Date of revision : 2020-07-17

Version : 3.01

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : Roko Professional Anti-Virus, Roko Professional Anti-Virus Aloe

Chemical name : Mixture.

EC number : Mixture.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Fluid for hygienic disinfection of hands by rubbing with bactericidal properties, fungicides and virucides; for use in the medical field and demanding areas compliance with the appropriate level of hygiene - in the food industry, public utilities, in industrial and domestic conditions, as well as for disinfecting surfaces and devices having as well as not in contact with food.

#### 1.3 Details of the supplier of the safety data sheet

PCC Consumer Products Kosmet Sp. z o.o., ul. Sienkiewicza 4, 56-120 Brzeg Dolny, Poland

Telephone: +48 71 794 2741; Fax: +48 71 794 2879

E-mail address of person responsible for this SDS: msds@kosmet.com.pl

#### 1.4 Emergency telephone number

##### National advisory body/Poison Center

Telephone number : Not available.

##### Supplier

Telephone number : Telephone: +48 71 794 2555, +48 71 794 2441 (available 24h/day) or +48 71 794 2690 (fax) at PCC Rokita SA or the closest local Fire Brigade

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225

Eye Irrit. 2, H319

STOT SE 3, H336


The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 - Highly flammable liquid and vapor.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.

## Precautionary statements

<b>General</b>	: Read label before use. If medical advice is needed, have product container or label at hand.
<b>Prevention</b>	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>Response</b>	: IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or physician if you feel unwell.
<b>Storage</b>	: Store in a well-ventilated place. Store in a closed container.
<b>Disposal</b>	: Dispose of contents/container to appropriate places in accordance with applicable regulations.
<b>Hazardous ingredients</b>	: Not applicable.
<b>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</b>	: Not applicable.

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** :

**Other hazards which do not result in classification** : This product is a biocidal product as defined in EU Regulation 528/2012.

## SECTION 3: Composition/information on ingredients

**3.1 Substance** : Not applicable.

### 3.2 Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
ethanol	REACH #: 01-2119457610-43 EC: 200-578-6 CAS: 64-17-5	≥50 - ≤75	Flam. Liq. 2, H225 Eye Irrit. 2, H319	[1] [2]
butanone	EC: 201-159-0 CAS: 78-93-3 Index: 606-002-00-3	<1	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	[1] [2]
propan-2-ol	EC: 200-661-7 CAS: 67-63-0 Index: 603-117-00-0	<1	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336  <b>See Section 16 for the full text of the H statements declared above.</b>	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

## Biocidal Products Directive

### Active substances

Name	Concentration
Ethanol (ethyl alcohol)	70 g/100 g

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : After exposure in this way, no harmful effects are expected. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : Can cause central nervous system (CNS) depression.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

## SECTION 5: Firefighting measures

---

### 5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Hazardous combustion products : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

### 5.3 Advice for firefighters

Special precautions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

---

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other sections : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### Seveso Directive - Reporting thresholds (in tonnes)

##### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonne	50000 tonne

### 7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
ethanol	<b>Regulation of the Minister of Family, Labor and Social Policy (J of Laws 2018, item 1286) (Poland, 7/2018).</b> TWA: 1900 mg/m <sup>3</sup> 8 hours.
glycerol	<b>Regulation of the Minister of Family, Labor and Social Policy (J of Laws 2018, item 1286) (Poland, 7/2018).</b> TWA: 10 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction
butanone	<b>Regulation of the Minister of Family, Labor and Social Policy (J of Laws 2018, item 1286) (Poland, 7/2018). Absorbed through skin.</b> TWA: 450 mg/m <sup>3</sup> 8 hours. STEL: 900 mg/m <sup>3</sup> 15 minutes.
propan-2-ol	<b>Regulation of the Minister of Family, Labor and Social Policy (J of Laws 2018, item 1286) (Poland, 7/2018). Absorbed through skin.</b> TWA: 900 mg/m <sup>3</sup> 8 hours.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs**

Product/ingredient name	Type	Exposure	Value	Population	Effects
ethanol	DNEL	Long term Oral	87 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	114 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	206 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	343 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	950 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	950 mg/m <sup>3</sup>	Workers	Systemic
glycerol	DNEL	Short term Inhalation	1900 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	33 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	56 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Oral	229 mg/kg bw/day	General population	Systemic
butanone	DNEL	Long term Oral	31 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	106 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	412 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	600 mg/m <sup>3</sup>	Workers	Systemic
propan-2-ol	DNEL	Long term Dermal	1161 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Oral	26 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	89 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	319 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	500 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	888 mg/kg bw/day	Workers	Systemic

**PNECs**

No PNECs available.

**8.2 Exposure controls**

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical product, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.



## Skin protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Wear suitable gloves tested to EN374.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## **SECTION 9: Physical and chemical properties**

---

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Color** : Colorless.
- Odor** : Characteristic.
- Odor threshold** : Lack of data.
- pH** : 6 - 8
- Melting point/freezing point** : Lack of data.
- Initial boiling point and boiling range** : Not available.
- Flash point** : Closed cup: 17°C
- Evaporation rate** : Lack of data.
- Flammability (solid, gas)** : Lack of data.
- Upper/lower flammability or explosive limits** : Lack of data.
- Vapor pressure** : Lack of data.
- Vapor density** : Lack of data.
- Density** : 0,8 - 1,0 g/cm<sup>3</sup> [20°C]
- Relative density** : Lack of data.
- Solubility(ies)** : Easily soluble in the following materials: cold water and hot water.
- Solubility in water at room temperature (g/l)** : Lack of data.
- Partition coefficient: n-octanol/water** : Lack of data.
- Auto-ignition temperature** : Lack of data.
- Decomposition temperature** : Lack of data.
- Viscosity** : Lack of data.
- Explosive properties** : Lack of data.
- Oxidizing properties** : None.
- Additional information** : Lack of data.

### 9.2 Other information

No additional information.

Note: Integers (i.e. 3 or 7) should be read as decimals (3.0 or 7.0)

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : Flammable, in the presence of open flames, sparks, discharges and heat.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : ignition and ignition sources, high temperature
- 10.5 Incompatible materials** : oxidizing agents
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	7 g/kg	-
glycerol	LD50 Oral	Rat	12600 mg/kg	-
	LD50 Dermal	Rabbit	6480 mg/kg	-
butanone	LD50 Oral	Rat	2737 mg/kg	-
	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-

#### Acute toxicity estimates

Not available.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Moderate irritant	Rabbit	-	0,066666667 minutes 100 mg	-
	Eyes - Moderate irritant	Rabbit	-	100 Ul	-
	Eyes - Severe irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	400 mg	-
glycerol	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
butanone	Skin - Mild irritant	Rabbit	-	24 hours 14 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
propan-2-ol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Moderate irritant	Rabbit	-	10 mg	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

**Conclusion/Summary** : Not available.

#### Sensitizer

**Conclusion/Summary** : Not available.



### Mutagenicity

Conclusion/Summary : Not available.

### Carcinogenicity

Conclusion/Summary : Not available.

### Reproductive toxicity

Conclusion/Summary : Not available.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Mixture.	Category 3	-	Narcotic effects
butanone	Category 3	-	Narcotic effects
propan-2-ol	Category 3	-	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

### Potential acute health effects

**Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

**Ingestion** : Can cause central nervous system (CNS) depression.

**Skin contact** : No known significant effects or critical hazards.

**Eye contact** : Causes serious eye irritation.

### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness

**Ingestion** : No specific data.

**Skin contact** : No specific data.

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

#### Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

## **SECTION 12: Ecological information**

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure	
ethanol	Acute EC50 17,921 mg/l Marine water	Algae - Ulva pertusa	96 hours	
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours	
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours	
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days	
	Chronic NOEC 4,995 mg/l Marine water	Algae - Ulva pertusa	96 hours	
	Chronic NOEC 100 µl/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days	
	Chronic NOEC 0,375 µl/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks	
	Acute EC50 >500000 µg/l Marine water	Algae - Skeletonema costatum	96 hours	
	butanone			

propan-2-ol	Acute EC50 5091000 µg/l Fresh water	Daphnia - Daphnia magna - Larvae	48 hours
	Acute LC50 3220000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute EC50 1000 mg/l	Aquatic plants - Scenedesmus subspicatus	72 hours
	Acute EC50 13299 mg/l	Daphnia - Daphnia magna	48 hours
	Acute EC50 7550 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 9640 mg/l	Fish - Pimephales promelas	96 hours

## 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

## 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
ethanol	-0,35	-	low
glycerol	-1,76	-	low
butanone	0,3	-	low
propan-2-ol	0,05	-	low

## 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

## 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

# SECTION 13: Disposal considerations

## 13.1 Waste treatment methods

### Product

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional or local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

### European waste catalogue (EWC)

Waste code	Waste designation
16 03 05*	organic wastes containing hazardous substances




### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Barrel	15 01 10* packaging containing residues of or contaminated by hazardous substances
Bottle	15 01 10* packaging containing residues of or contaminated by hazardous substances
Container	15 01 10* packaging containing residues of or contaminated by hazardous substances

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	UN1993	UN1993	UN1993
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (ethanol)	Flammable Liquid, n.o.s (incl. ethanol) (ethanol)	Flammable Liquid, n.o.s (incl. ethanol) (ethanol)
14.3 Transport hazard class(es)	3 	3 	3 
14.4 Packing group	II	II	II
14.5 Environmental hazards	No.	No.	No.
Additional information	<u>Special provisions</u> 601 <u>Tunnel code</u> (D/E)	-	The environmentally hazardous substance mark may appear if required by other transportation regulations. <u>Quantity limitation</u> Passenger and Cargo Aircraft: 5 L. Packaging instructions: 353. Cargo Aircraft Only: 60 L. Packaging instructions: 364.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REGULATION (EC) NO 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

The European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID) constituting Appendix C to the Convention concerning International Carriage by Rail (COTIF)

International Maritime Dangerous Goods Code (IMDG CODE)

IATA /International Air Transport Association/ Dangerous Goods Regulations (IATA DGR)

Ordinance of the Minister of Labour and Social Policy of 12 June 2018 concerning maximum permissible concentrations and intensities of agents harmful to health in a work environment (Journal of Laws 2018 item 1286).

Act of 9 October 2015 on biocidal products (Journal of Laws item 1926, 2015)

REGULATION (EU) No 528/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 22 May 2012 concerning the making available on the market and use of biocidal products

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Act on Waste of 14 December 2012 (Dz. U. /Journal of Laws/ of 2013, No. 0, item 21)

Act on Packaging and Packaging Waste Management of 13 June 2013 (Dz. U. /Journal of Laws/ of 2013, No. 0, item 888)

Act on Chemical Substances and Their Mixtures of 25 February 2011 (Dz. U. /Journal of Laws/ No. 63, item 322)

Regulation of the Minister of Labour and Social Policy on the general occupational health and safety regulations of 26 September 1997 (Dz. U. /Journal of Laws/ of 2003, No. 169, item 1650 as amended)

#### **Annex XIV - List of substances subject to authorization**

##### **Annex XIV**

None of the components are listed.

##### **Substances of very high concern**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### **Other EU regulations**

**Europe inventory** : All components are listed or exempted.

##### **Seveso Directive**

This product is controlled under the Seveso Directive.

##### **Danger criteria**

<b>Category</b>
P5c

#### **Biocidal Products Directive**

**Authorization number** : 8047/2020

**Product type** : Liquid.

Avoid exposure. After accidental exposure, seek immediate medical attention. Do not induce vomiting.

Product waste and emptied containers should be disposed of in accordance with local waste regulations. Do not reuse container.

Do not allow to enter drains or watercourses.

**15.2 Chemical Safety Assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## **SECTION 16: Other information**

---

**Changes to the Safety Data Sheet** :

**Training advice** : Ensure operatives are trained to minimise exposures.

**Abbreviations and acronyms** :

- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- CAS = Chemical Abstracts Service
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- CMR = Carcinogen, Mutagen or Reproductive toxicant
- CSA = Chemical Safety Assessment
- CSR = Chemical Safety Report
- DNEL = Derived No Effect Level
- EC number = EINECS or ELINCS number
- EC50 = Half maximal effective concentration

ES = Exposure Scenario  
 EUH statement = CLP-specific Hazard statement  
 EWC = European Waste Catalogue  
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 H statement = CLP/GHS Hazard statement  
 IATA = International Air Transport Association  
 IC50 = Half maximal inhibitory concentration  
 IMDG = International Maritime Dangerous Goods  
 LC50 = Median lethal concentration  
 LD50 = Median lethal dose  
 LogPow = logarithm of the octanol/water partition coefficient  
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
 OECD = Organisation for Economic Co-operation and Development  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]  
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
 RRN = REACH Registration Number  
 STOT = Specific Target Organ Toxicity  
 SVHC = Substances of Very High Concern  
 VOC = Volatile Organic Compound  
 vPvB = Very Persistent and Very Bioaccumulative

**Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Classification	Justification
Flam. Liq. 2, H225	Expert judgment
Eye Irrit. 2, H319	Expert judgment
STOT SE 3, H336	Expert judgment

**Full text of abbreviated H statements** : H225  
 H319  
 H336  
 Highly flammable liquid and vapor.  
 Causes serious eye irritation.  
 May cause drowsiness or dizziness.

**Full text of classifications [CLP/GHS]** : Eye Irrit. 2  
 Flam. Liq. 2  
 STOT SE 3  
 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 FLAMMABLE LIQUIDS - Category 2  
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

**Notice to reader**

The information contained herein is accurate to the latest knowledge and describes the product from the point of view of help and environmental protection as well as safe handling. The information presented in this SDS refers to the technical product only and will not apply to any processed product. Final determination of the suitability of any materials for the chosen application(s) is the sole responsibility of the user"